

AMENDMENTS TO THE CLAIMS

The following listing of claims replaces all previous versions and listing of claims, which were previously presented in the instant application.

Listing of the Claims:

1. (currently amended) A wireless communication system, comprising:
a programmable interface coupleable between a device and a transmitter, the interface being operable to receive device data from the device and to provide user-configurable device data to the transmitter; and
a programming station selectively coupleable to the interface to enable a user to program the interface to provide the user-configurable device data to the transmitter.
2. (original) The system as recited in claim 1, wherein the device data comprises operational data of the device.
3. (currently amended) The system as recited in claim 1, wherein the device data is processed ~~received~~ by the interface at periodic intervals.
4. (currently amended) The system as recited in claim 3, wherein the programming station enables a user to establish the periodic interval that data is processed ~~received~~ by the interface.
5. (currently amended) The system as recited in claim 1, wherein the user-configurable device data comprises operational data of the device that is processed by the interface in response to programming provided by the programming station.

6. (original) The system as recited in claim 5, wherein the desired device data comprises a sum of operational data of the device received by the interface periodically.

7. (original) The system as recited in claim 6, wherein the programming station enables the wireless communication system user to reset the sum.

8. (original) The system as recited in claim 1, wherein the programming station comprises a computer system coupleable to the interface.

9. (original) The system as recited in claim 8, further comprising a cell controller and an antenna.

10. (original) The system as recited in claim 9, wherein the cell controller is coupled to the computer system.

11. (original) The system as recited in claim 1, wherein the transmitter is a transponder.

12. (currently amended) An interface for a wireless communication system, comprising a processor, wherein the processor interface is operable to receive a first set of device data from a device and to provide a second set of device data configured by a user from the first set of data to the a transmitter, further wherein the interface is operable to enable a system user to configure at least a portion of the second set of data provided to the transmitter.

13. (currently amended) The interface as recited in claim 12, wherein the ~~interface-processor~~ is operable to process the first set of device data received from the device, further wherein the at least a portion of the second set of user-configured device data comprises data processed by the interface.

14. (original) The interface as recited in claim 12, wherein the interface is programmable to enable a user to provide programming to the interface to direct the operation of the interface.

a2 15. (currently amended) The interface as recited in claim 14, wherein the interface is coupleable to a programming station, the programming station being operable to provide the interface with programming to enable the ~~interface-processor~~ to communicate with the device using a first communication protocol and with the transmitter using a second communication protocol.

16. (original) The interface as recited in claim 14, wherein the interface is operable to be programmed to communicate with a first device using a first communication protocol and then re-programmed to communicate with a second device using a different communication protocol.

17. (currently amended) The interface as recited in claim 12, wherein the first set of device data comprises device operating data.

18. (original) The interface as recited in claim 17, wherein the interface is operable to enable a user to select desired device operating data to be provided to the transmitter.

19. (currently amended) The interface as recited in claim 12, wherein the at least a portion of the second set of user-configured device data is an ongoing count of a device operating parameter.

20. (original) The interface as recited in claim 12, wherein the interface comprises a first electrical connector configured for mating engagement with a first external electrical connector coupled to a programming system.

21. (original) The interface as recited in claim 20, wherein the interface comprises a second electrical connector configured for mating engagement with a second external electrical connector coupled to the device.

A2
22. (original) The interface as recited in claim 12, wherein the transmitter is a transponder.

23. (original) The interface as recited in claim 21, wherein the interface comprises a third electrical connector configured for mating engagement with the transmitter.

24. (currently amended) A method of operating a wireless communication system to enable a system user to configure device data communicated by a transmitter coupled to a device, comprising the acts of:

connecting a programmable interface to a programming station operated by a system user;

operating the programming station to configure the programming of the programmable interface to receive the device data and to provide the a user-configured set of device data to the transmitter in a user-selected configuration; and

coupling the programmable interface between the device and the transmitter.

25. (original) The method as recited in claim 24, further comprising the act of transmitting a unique identifier for the transmitter with the data from the device.

26. (original) The method as recited in claim 24, further comprising:
reconnecting the programmable interface to the programming station; and
operating the programming station to reconfigure the programming of the programmable interface to provide the device data in a different user selected configuration.

27. (currently amended) A method of operating a wireless communication system to enable a system user to configure data communicated from a medical asset by a transmitter, comprising the acts of:

A2 connecting a programmable interface to a programming station operated by a system user;

operating the programming station to configure the programming of the programmable interface to provide the data a cumulative total of a selected device parameter to the transmitter ~~from the medical asset in a configuration selected by the system~~ user; and

coupling the programmable interface between the medical asset and the transmitter.

28. (original) The method as recited in claim 27, further comprising the act of transmitting a unique identifier for the transmitter with the data from the device.

29. (original) The method as recited in claim 27, further comprising:
reconnecting the programmable interface to the programming station; and
operating the programming station to reconfigure the programming of the programmable interface to provide the data in a different configuration selected by the system user.

a2

30. (original) The method as recited in claim 27, wherein operating the programming station comprises establishing an interval that a medical asset parameter is to be monitored by the programmable interface.
